

CP2.5P



CP2.5PJ



CP2.5PD



Dimensions & Weight

	Stackable Terminal Plug	Terminal Plug with Jumper Slot	Dual Terminal Plug with Jumper Slot
Width	5 mm	5 mm	5 mm
Length	17.4 mm	20.9 mm	33 mm
Height	42.0 mm	42.0 mm	42.0 mm
Weight per piece	7.8 g	7.4 g	9.5 g

Technical Data/Ratings

Approvals						
Wire Size (solid / stranded)	12 AWG	0.2-2.5 mm ²	12 AWG	0.2-2.5 mm ²	12 AWG	0.2-2.5 mm ²
Voltage Rating	300 V	500 V	300 V	500 V	300 V	500 V
Current Rating	20 A	24 A	20 A	24 A	20 A	24 A
Insulation Material	Polyamide 66		Polyamide 66		Polyamide 66	

Installation Instructions

Wire Stripping Length	10 mm	10 mm	10 mm
Screwdriver	Flat Head 0.5 x 3 mm	Flat Head 0.5 x 3 mm	Flat Head 0.5 x 3 mm

Terminal Blocks

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Grey (standard) Start Element	CP2.5P	50	CP2.5PJ	50	CP2.5PD	50
Last Element	CP2.5PL	50	CP2.5PJL	50	CP2.5PDL	50
2 pole	CP2.5P/2	50	CP2.5PJ/2	50	CP2.5PD/2	50
3 pole	CP2.5P/3	50	CP2.5PJ/3	50	CP2.5PD/3	50
4 pole	CP2.5P/4	50	CP2.5PJ/4	50	CP2.5PD/4	50
5 pole	CP2.5P/5	50	CP2.5PJ/5	50	CP2.5PD/5	50
6 pole	CP2.5P/6	25	CP2.5PJ/6	25	CP2.5PD/6	25
7 pole	CP2.5P/7	25	CP2.5PJ/7	25	CP2.5PD/7	25
8 pole	CP2.5P/8	25	CP2.5PJ/8	25	CP2.5PD/8	25
9 pole	CP2.5P/9	25	CP2.5PJ/9	25	CP2.5PD/9	25
10 pole	CP2.5P/10	25	CP2.5PJ/10	25	CP2.5PD/10	25
11 pole	CP2.5P/11	10	CP2.5PJ/11	10	CP2.5PD/11	10
12 pole	CP2.5P/12	10	CP2.5PJ/12	10	CP2.5PD/12	10
13 pole	CP2.5P/13	10	CP2.5PJ/13	10	CP2.5PD/13	10
14 pole	CP2.5P/14	10	CP2.5PJ/14	10	CP2.5PD/14	10
15 pole	CP2.5P/15	10	CP2.5PJ/15	10	CP2.5PD/15	10

Accessories

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	
DIN Rail			2511120	20	2511120	20	
			CA701-15/S	20	CA701-15/S	20	
Shorting Link/ Jumpers	2 pole	JX2.5/2	100	JX2.5/2	100	JX2.5/2	100
	3 pole	JX2.5/3	50	JX2.5/3	50	JX2.5/3	50
	4 pole	JX2.5/4	50	JX2.5/4	50	JX2.5/4	50
	5 pole	JX2.5/5	50	JX2.5/5	50	JX2.5/5	50
	6 pole	JX2.5/6	10	JX2.5/6	10	JX2.5/6	10
	7 pole	JX2.5/7	10	JX2.5/7	10	JX2.5/7	10
	8 pole	JX2.5/8	10	JX2.5/8	10	JX2.5/8	10
	10 pole	JX2.5/10	10	JX2.5/10	10	JX2.5/10	10
	20 pole	JX2.5/20	10	JX2.5/20	10	JX2.5/20	10
DIN Mounting Foot	–	–	–	–	–	–	
Locking Clip	CXPLN	25	CXPLN	25	CXPLN	25	
Strain Relief	2 Way	CXSR2N	25	CXSR2N	25	CXSR2N	25
	4 Way	CXSR4N	25	CXSR4N	25	CXSR4N	25
Coding Pin	–	–	–	–	–	–	
Marking Tag	MC5	1 card (84 tags)	MC5	1 card (84 tags)	MC5	1 card (84 tags)	